




Product Description: ELumi™ 12W Non Dimmable Downlight

A perfect solution for new commercial applications or upgrading from compact fluorescent fittings in existing applications, the ELumi™ downlight is equipped with an opal diffuser to evenly distribute light.


SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-DLE412/40	12	4000	1400	117	100	White	Non Dimmable

Line Drawing



Polar Curve

Colour



White

Feature & Benefits

- IP54 rated
- TP(a) rated
- Opal diffuser for even light distribution
- Supplied with remote non-dimmable constant current driver
- 5 Year Warranty
- 3 year onsite warranty (registration required) *Terms and conditions apply

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP54
Lifetime L70 (hrs)	50000hrs	Lifetime L80 (Hours)	50000hrs
IK Rating	IK02	Overall Diameter (mm)	145
Weight (Kg)	0.387	Height (mm)	53
Product Type	Downlights	Cutout Diameter (mm)	120-130
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.