


Product Description:

ELumi™ 18W Non Dimmable Downlight

A perfect solution for new commercial applications or upgrading from compact fluorescent fittings in existing applications, the ELumi<sup>TM</sup> downlight is equipped with an opal diffuser to evenly distribute light.

| SKU Code     | Wattage | Colour   | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type     |
|--------------|---------|----------|--------|-------------|------------|---------------|--------------|
| AU-DLE618/40 | 18      | 4000     | 2040   | 114         | 100        | White         | Non Dimmable |
|              |         |          |        |             |            |               |              |
|              |         |          |        |             |            |               |              |
| Line Drawing |         | Polar Cu | urve   |             | Colour     |               |              |
|              |         |          |        |             |            |               |              |



## Feature & Benefits

- IP54 rated
- TP(a) rated
- Opal diffuser for even light distribution
- Supplied with remote nondimmable constant current driver
- 5 Year Warranty
- 3 year onsite warranty (registration required) \*Terms and conditions apply

## **Product Specs:**

| Input Voltage            | 220~240V AC |  |  |
|--------------------------|-------------|--|--|
| Power Factor             | 0.9         |  |  |
| Lifetime L80 (Hours)     | 50000hrs    |  |  |
| Overall Diameter (mm)    | 190         |  |  |
| Height (mm)              | 53          |  |  |
| Cutout Diameter (mm)     | 160-170     |  |  |
| Operating Temp. (Max) °C | 40°C        |  |  |

| Input Frequency          | 50/60HZ    |  |  |
|--------------------------|------------|--|--|
| IP Rating                | IP54       |  |  |
| IK Rating                | IK02       |  |  |
| Weight (Kg)              | 0.540      |  |  |
| Product Type             | Downlights |  |  |
| Operating Temp. (Min) °C | -20°C      |  |  |
|                          |            |  |  |

## Compliance & Approvals:







## vvarranty

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.