

Product Description: MR11 Adjustable Fire Rated Downlight

SKU Code	Finish Colour
AU-DLL692PB	Polished Brass
AU-DLL692PC	Polished Chrome
AU-DLL692SN	Satin Nickel
AU-DLL692W	White

Line Drawing

Polar Curve

Colour

#### Feature & Benefits

- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Requires a suitable 12V Constant Voltage Transformer (Not Included)
- UK Patent GB2426321
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Lamp not included

## Product Specs:

Input Voltage	12~12V AC	Lifetime L70 (hrs)	3000hrs
Lamp Base	GU4.0	Overall Diameter (mm)	75
Weight (Kg)	0.225	Height (mm)	115
Cutout Diameter (mm)	60-		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.