Product Description: MR16 Fixed Fire Rated Downlight

SKU Code	Beam Angle
AU-DLL971	36

Line Drawing

Polar Curve

Colour

Feature & Benefits

- UK Patent GB2426321
- Screw thread lock ring provides sharp 'scallop' light effect
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- These products available in an Anodised finish only
- 2 Year guarantee

Product Specs:

Input Voltage	12~12V AC
Lamp Base	GU5.3
Weight (Kg)	0.245
Cutout Diameter (mm)	65-

Lifetime L70 (hrs)	3000hrs
Overall Diameter (mm)	80
Height (mm)	115

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.