

Product Description:

White GU10 Fixed Fire Rated Downlight - 75mm cutout

Range of aluminium fixed GU10 compact fire rated downlights. Rated to 30, 60 and 90 minute fire ceilings. Complies with BS476 Part 21 and BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics). Fire and Acoustic rated. Not for use with dichroic halogen lamps (cool beam). Lamp not included.

| SKU Code    | Finish Colour   |
|-------------|-----------------|
| AU-DLM901MW | Matt White      |
| AU-DLM901PB | Polished Brass  |
| AU-DLM901PC | Polished Chrome |
| AU-DLM901SN | Satin Nickel    |
| AU-DLM901SS | Satin Silver    |
| AU-DLM901W  | White           |

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Registered Community Design 390612-0001/2/3
- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Reduced recess depth for shallow ceiling voids
- Not for use with dichroic halogen (cool beam) lamps
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Lamp not included

## Product Specs:

|                       |             |                 |                                  |
|-----------------------|-------------|-----------------|----------------------------------|
| Input Voltage         | 220~240V AC | Input Frequency | 50/60HZ                          |
| IP Rating             | IP20        | Lamp Base       | GU10                             |
| Overall Diameter (mm) | 85          | Weight (Kg)     | 0.285                            |
| Height (mm)           | 107         | Product Type    | Downlights, Fire-Rated Downlight |
| Cutout Diameter (mm)  | 75-         |                 |                                  |

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.