

Product Description:

GU10 Adjustable Compact Fire Rated Downlights 85mm cutout

Fixed GU10 Compact Fire Rated Downlight with an integrated intumescent material that completely seals the downlight and cut-out in the event of a fire. Downlight has been tested in 30,60 and 90 minute fire rated ceilings. Reduced recess depth in order to be suitable for shallow ceiling voids. Cast aluminium and pressed steel body. Available in a number of different finish colours, White, Polished Chrome and Satin Nickel. IP20 rated downlight. Not for use with dichroic halogen lamps. Lamp not included.

| SKU Code | Wattage | Finish Colour |
|-------------|---------|-----------------|
| AU-DLM902MW | | Matt White |
| AU-DLM902PB | 50 | Polished Brass |
| AU-DLM902PC | | Polished Chrome |
| AU-DLM902SN | | Satin Nickel |
| AU-DLM902SS | | Satin Silver |
| AU-DLM902W | | White |

Line Drawing Polar Curve Colour

Feature & Benefits

- Registered Community Design 390612-0001/2/3
- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Reduced recess depth for shallow ceiling voids
- Not for use with dichroic halogen (cool beam) lamps
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Optional MR16 lampholder (AU-0501F) available for flexibility of lamp choice
- Lamp not included

Product Specs:

| Input Voltage | 220~240V AC |
|---------------|---------------------------------|
| IP Rating | IP20 |
| Lamp Base | GU10 |
| Weight (Kg) | 0.316 |
| Product Type | Downlights,Fire-Rated Downlight |

| Input Frequency | 50/60HZ |
|-----------------------|---------|
| Lifetime L70 (hrs) | 5000hrs |
| Overall Diameter (mm) | 95 |
| Height (mm) | 107 |
| Cutout Diameter (mm) | 85- |

Compliance & Approvals:









Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.