

Product Description:

GU10 Adjustable Fire Rated Downlight

| SKU Code | Beam Angle |
|-----------|------------|
| AU-DLM962 | 36 |

Line Drawing Polar Curve Colour

Feature & Benefits

- UK Patent GB2426321
- Screw thread lock ring provides sharp 'scallop' light effect
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
 - Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- These products available in an Anodised finish only
- 2 Year guarantee

Product Specs:

| Input Voltage | 220~240V AC |
|----------------------|-------------|
| Lamp Base | GU10 |
| Weight (Kg) | 0.368 |
| Cutout Diameter (mm) | 80- |

| Lifetime L70 (hrs) | 5000hrs |
|-----------------------|---------|
| Overall Diameter (mm) | 95 |
| Height (mm) | 115 |

Compliance & Approvals:









Warranty

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.