



Product Description: 60-400W 1 Gang 2 Way Zero Cross Rotary Dimmer

1 Gang 2 Way Zero Cross Rotary Dimmer Module


SKU Code

AU-DSP400X

Line Drawing

Polar Curve

Colour



Feature & Benefits

- Suitable for control of dimmable compact fluorescent and LED lamps, dimmable electronic transformers, LED drivers, toroidal transformers and tungsten lamps
- Integrated trimming potentiometer allows CFL and LED lamps to be set at a minimum level to prevent them going out or flickering at the bottom of the dimmer range
- Leading edge phase control
- For use with resistive and inductive loads
- Integrated over-temperature protection fuse
- Module case ultrasonically sealed to reduce dimmer buzzing
- Smooth dimming operation from 0-100% light output
- May be fitted to most dimmer plates
- One or two way switching
- Derate Dimmer by 70% for LED loads
- 1 year warranty

Product Specs:

Input Voltage	220~240V AC	Width (mm)	26
Length (mm)	62	Weight (Kg)	0.054
Height (mm)	25		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.