

Product Description: 5-400W Trailing Edge Dimmer


SKU Code

AU-DSPS402T

Line Drawing

Polar Curve

Colour



## Feature & Benefits

- Module case ultrasonically sealed to reduce dimmer buzzing
- Integrated over-temperature protection fuse
- Trailing edge dimmer module suitable to control dimmable electronic transformers and tungsten lamps WITHOUT de-rating
- Not suitable for use with fluorescent lamps
- Integrated trimming potentiometer allows CFL and LED lamps to be set at a minimum level to prevent lamps flickering or extinguishing & maintain lamp life
- Trailing edge phase control
- For use with resistive and capacitive loads
- Electrical Safety - BS EN 60669-2-1:2004+A12:2010
- One or two way switching
- May be fitted to most dimmer plates
- EMC compliance - BS EN 55015:2006+A2:2009
- Smooth dimming operation from 0-100% light output
- De-rating for LED -  $2/3$  of load x load PF = max load on dimmer
- De-rating for CFL -  $1/3$  of load x load PF = max load on dimmer
- No de-rating for halogen loads

## Product Specs:

Input Voltage	220~240V AC	Width (mm)	25
Length (mm)	62	Height (mm)	23.5

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.