


## Product Description: Ecylps 14W Fixed Downlight


Part of the Eclyps range, the 14W Fixed COB LED Downlights are ideal for commercial lighting installations, including circulation and break out areas. With a lumen package of 1280lm, spaces are further enhanced by applying Eclyps accessories such as Mirror, Black or Silver Matt baffles, Honeycomb attachments or colour filters. Supplied with CRI80 as standard and SDCM<3, clients can also opt for CRI90 options to further enhance colour quality of the installation. Beam angles include 15°, 24°, 36° and 60°. L70 is 50,000 hrs.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|---|---|---|---|---|---|---|
| AU-EC14F1DTAK/30 | 14 | 3000 | 1280 | 92 | 15 | White |
| AU-EC14F1DTAK/40 | 14 | 4000 | 1280 | 92 | 15 | White |
| AU-EC14F1EMNDAK/30 | 14 | 3000 | 1280 | 92 | 15 | White |
| AU-EC14F1EMNDAK/40 | 14 | 4000 | 1280 | 92 | 15 | White |
| AU-EC14F1NDAK/30 | 14 | 3000 | 1280 | 92 | 15 | White |
| AU-EC14F1NDAK/40 | 14 | 4000 | 1280 | 92 | 15 | White |
| AU-EC14F2DTAK/30 | 14 | 3000 | 1280 | 92 | 24 | White |
| AU-EC14F2DTAK/40 | 14 | 4000 | 1280 | 92 | 24 | White |
| AU-EC14F2EMNDAK/30 | 14 | 3000 | 1280 | 92 | 24 | White |
| AU-EC14F2EMNDAK/40 | 14 | 4000 | 1280 | 92 | 24 | White |
| AU-EC14F2NDAK/30 | 14 | 3000 | 1280 | 92 | 24 | White |
| AU-EC14F2NDAK/40 | 14 | 4000 | 1280 | 92 | 24 | White |
| AU-EC14F3DTAK/30 | 14 | 3000 | 1280 | 92 | 36 | White |
| AU-EC14F3DTAK/40 | 14 | 4000 | 1280 | 92 | 36 | White |
| AU-EC14F3EMNDAK/30 | 14 | 3000 | 1280 | 92 | 36 | White |
| AU-EC14F3EMNDAK/40 | 14 | 4000 | 1280 | 92 | 36 | White |
| AU-EC14F3NDAK/30 | 14 | 3000 | 1280 | 92 | 36 | White |
| AU-EC14F3NDAK/40 | 14 | 4000 | 1280 | 92 | 36 | White |
| AU-EC14F6DTAK/30 | 14 | 3000 | 1280 | 92 | 60 | White |
| AU-EC14F6DTAK/40 | 14 | 4000 | 1280 | 92 | 60 | White |
| AU-EC14F6EMNDAK/30 | 14 | 3000 | 1280 | 92 | 60 | White |
| AU-EC14F6EMNDAK/40 | 14 | 4000 | 1280 | 92 | 60 | White |
| AU-EC14F6NDAK/30 | 14 | 3000 | 1280 | 92 | 60 | White |
| AU-EC14F6NDAK/40 | 14 | 4000 | 1280 | 92 | 60 | White |


## Line Drawing





## Polar Curve




15° Fixed



24° Fixed



36° Fixed



60° Fixed

## Colour

## Feature & Benefits

- Non Dimmable
- CRI 80 (Selected CRI 90 options available)
- SDCM < 3
- Beam angles available in 36°, 60° with 15° & 24° to special order
- Baffle/Filter/Reflector accessories available
- Ideal for Commercial and Hospitality
- 5 Year Warranty

## Product Specs:

| | | | |
|---|---|---|---|
| Input Voltage | 220~240V AC | Input Frequency | 50/60HZ |
| Power Factor | 0.95 | IP Rating | IP20 |
| Lifetime L70 (hrs) | 50000hrs | Overall Diameter (mm) | 113 |
| Cutout Width (mm) | 100 | Height (mm) | 106 |
| Product Type | Downlights | Cutout Diameter (mm) | 100-105 |
| Operating Temp. (Min) °C | -20°C | Operating Temp. (Max) °C | 50°C |

## Compliance & Approvals:

## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.