



SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour
AU-EC14PA2DTAK/30	3000	560	40	14	20	White
AU-EC14PA2DTAK/40	4000	560	40	14	20	White
AU-EC14PA2EMNDAK/30	3000	560	40	14	20	White
AU-EC14PA2EMNDAK/40	4000	560	40	14	20	White
AU-EC14PA2NDAK/30	3000	560	40	14	20	White
AU-EC14PA2NDAK/40	4000	560	40	14	20	White
AU-EC14PA3DTAK/30	3000	560	40	14	30	White
AU-EC14PA3DTAK/40	4000	560	40	14	30	White
AU-EC14PA3EMNDAK/30	3000	560	40	14	30	White
AU-EC14PA3EMNDAK/40	4000	560	40	14	30	White
AU-EC14PA3NDAK/30	3000	560	40	14	30	White
AU-EC14PA3NDAK/40	4000	560	40	14	30	White

Line Drawing

Polar Curve

Color

Product Features:

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.8	Dimmable	No
Number of LEDs	1	IP Rating	IP20
Technology	LED	Luminaire Distribution	Direct
Lifetime L70 (hrs)	50000	Dali	Yes
Operating Temp	50°C	Optic Material	Glass
Overall Diameter (mm)	96	Cutout Diameter (mm)	90
Recess Depth (mm)	96	Positional Adjustment	Adjustable
Positional Adjustment	Adjustable		

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.