

Product Description:

Includes LED driver and NiMH battery in a mesh sleeve. Compact downlight fits into a 44mm cut-out.

Product Image:



Fuente de alimentación de emergencia para módulos LED no mantenida: 240 V, 2 W, 3 horas de autonomía


Product Features:

- Non-maintained LED emergency train
- 3 Hour emergency duration
- 2W High power LED
- Includes LED driver and NiMH battery in a mesh sleeve
- Compact downlight fits into a 40mm cut-out
- LED module may also be mounted without downlight in a 20mm hole


Product Specs:

| | | | |
|-----------------------|-------|-------------------|----------|
| Technology | LED | Input Voltage | 220~240V |
| Number of LEDs | 1 | Dimmable | No |
| IP Rating | IP20 | Fire Protection | No |
| Overall Diameter (mm) | 51 | Recess Depth (mm) | 70 |
| Weight (Kg) | 0.283 | | |

Line Drawing



Polar Curve



SKU Table and Ordering:

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|----------|---------|--------|--------|-------------|------------|---------------|
| AU-EMLD2 | 2 | 6400 | 110 | 55 | 40 | Blanco |

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 ao. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.