

Product Description: 36W IP65 Adjustable Floodlight

| SKU Code | Wattage | Colour | Beam Angle |
|--------------|---------|--------|------------|
| AU-FLD361/65 | 36 | 6500 | 60 |

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 Mains voltage aluminium LED flood light
- Single colour and RGB versions available
- Powder coated corrosion resistant finish
- Tempered glass lens
- Horizontal adjustment 180°
- Vertical adjustment 65°
- 1m Rubber mains cables
- 1m Rubber mains & in/out signal cables for RGB versions
- Non-dimmable

Product Specs:

| | |
|--------------------|-------------|
| Input Voltage | 220~250V AC |
| Lifetime L70 (hrs) | 50000hrs |
| Length (mm) | 350 |
| Height (mm) | 64 |

| | |
|-------------|------|
| IP Rating | IP65 |
| Width (mm) | 64 |
| Weight (Kg) | 4.19 |

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.