

Product Description: Ostia™ 100W IP65 Dimmable Highbay

Range of highly efficient LED Highbay luminaires in 4000K (6000K to special order). 1-10V dimming function as standard allowing for installations with daylight or occupancy sensors. Fitted with 120° beam angle as standard, optional 60° or 90° beam angle available. Accessories include acrylic reflectors and suspension and wall mounting options. Supplied with a 1.5m mains cable.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-HB1001A/40	100	4000	8000	80	120	Satin Silver	Dimmable
AU-HB1001A/60	100	6000	10000	100	120	Satin Silver	Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Suitable for use in warehousing, manufacturing, conference centres, industrial lighting, canopies etc.
- Significant energy savings and reduced maintenance over HID highbays
- High thermal efficient aluminium heatsink - low operating temperature
- 1-10V dimming function built in as standard - allows for installation with daylight or occupancy sensors
- High power factor 0.95
- Instant on/off, no re-strike delay
- Low voltage constant current Meanwell driver
- IP65 sealed housing
- 120 degree beam as standard, optional 60 or 90 degree and acrylic reflectors available
- Suspension and wall mounting options
- Supplied with 3m of mains cable
- 6000K version delivering 100lm/W available to special order
- (L70) at a 50,000 hour lifetime
- 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	100~277V AC	Input Frequency	50/60HZ
Power Factor	0.95	IP Rating	IP65
Lifetime L70 (hrs)	50000hrs	IK Rating	IK08
Length (mm)	172	Overall Diameter (mm)	388
Weight (Kg)	6.396	Height (mm)	172
Product Type	Highbays	Operating Temp. (Min) °C	20°C
Operating Temp. (Max) °C	60°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.