

Product Description: Versitile™ 38W IP40 600 x 600mm Panel

Range of highly efficient award winning edge-lit LED light panels non-dimmable. Fitted with high transmission diffuser for minimal glare, UGR 19. Lightweight slim aluminium frame in RAL9016 White finish. IP rating of IP40 from the front of the panel and IP20 from the back. Suitable for installations in 15 and 24mm T-bar ceilings. May also be surface mounted or suspended with applicable accessories. Fitted with a connector to easily connect the light panel and the driver. Supplied with remote LED driver. EM on the end of a Sku stands for Emergency which comes with a battery pack for emergency lighting installations.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-LP100B/30	38	3000	3600	95	120	White
AU-LP100B/30D	38	3000	3600	95	120	White
AU-LP100B/30DEM	38	3000	3600	95	120	White
AU-LP100B/30EM	38	3000	3600	95	120	White
AU-LP100B/40	38	4000	3900	103	120	White
AU-LP100B/40D	38	4000	3900	103	120	White
AU-LP100B/40DEM	38	4000	3900	103	120	White
AU-LP100B/40EM	38	4000	3900	103	120	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Edge lit design provides superior light performance and uniformity ideal for offices and commercial lighting
- High transmission diffuser drastically reduces uncomfortable glare
- Heatsink rapidly dissipates heat through rear of fitting
- IP44 from below – suitable for use in commercial kitchens, clean rooms, health care and similar environments
- Suitable for installation in 15 & 24mm T-bar ceilings
- Panel frame RAL9016 White
- High colour rendering index (Ra) 80
- SDCM <4 providing consistent light colour quality
- (L70) at a 40,000 hour lifetime
- EM Emergency Lighting Options available

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP40
Lifetime L70 (hrs)	40000hrs	Width (mm)	595
Length (mm)	595	Weight (Kg)	4.416
Height (mm)	12	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	50°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.