




SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour
AU-LP101CAK/30	3000	3600	95	38	120	RAL9016
AU-LP101CAK/30EM	3000	3600	95	38	120	RAL9016
AU-LP101CAK/40	4000	3900	103	38	120	RAL9016
AU-LP101CAK/40EM	4000	3900	103	38	120	RAL9016

Line Drawing

Polar Curve

Color



Product Features:

- Edge lit design provides superior light performance and uniformity ideal for offices and commercial lighting
- High transmission diffuser drastically reduces uncomfortable glare
- Heatsink rapidly dissipates heat through rear of fitting
- Dimmable and CX colour exchange version available to set the desired light environment
- IP65 front and back – suitable for use in commercial kitchens, health care and similar environments
- Suitable for installation in 15 & 24mm T-bar ceilings
- Panel frame RAL9016 White
- High colour rendering index (Ra) 80
- SDCM <4 providing consistent light colour quality
- Emergency options available (L70) at a 50,000 hour lifetime
- 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	Dimmable	Yes
Number of LEDs	132	IP Rating	IP65
Technology	LED	Luminaire Distribution	Direct
Lifetime L70 (hrs)	50000	Dali	Yes
Operating Temp	25°C	Optic Material	PS
Width (mm)	595	Length (mm)	595
SDCM	4	LED Chip	2835

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.