

Product Description:

Versitile[™] 50W Colour Xchange 600 x 600mm Dimmable Panel

SKU Code		Wattage	Lumens
AU-LP102	Polar Curve	50 Colo	4000 ur
Feature & Benefits			
 A range of edge-lit LED flat panels for office and commercial lighting Suitable for installation in 15 & 24mm T-bar ceilings Panel frame RAL9016 White May also be surface mounted or suspended 	 All versions use optical polycarbonate for even light distribution Dimmable (1-10V) and CX options also available Up to 20 CX panels can be interconnected and controlled with a AU-DLED801C controller 	 IP44 from below when recessed mounted - suitable for use in commercial kitchens, clean rooms, healthcare and similar environments High colour rendering index (Ra) 80 UGR (unified glare rating) - 19 perfect for use in offices 	 call sales office for details Life to 70% lumen maintenance (L70) - 40,000 hours 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	110~240V AC	Lifetime L70 (hrs)	50000hrs
Width (mm)	595	Length (mm)	595
Weight (Kg)	4.5	Height (mm)	12

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.