

**Product Description:**

White colour Xchange Versatile™ LED light panel. Fitted with high transmission diffuser for minimum glare. Lightweight slim aluminium frame in RAL9016 White finish. A standard light switch may be used to switch between 4000K and 6500K. Available in 220-240V and 110-265V for worldwide installations (for 110-265V contact sales office). Suitable for installation in 15 and 24mm T-bar ceilings. May also be surface mounted or suspended. Fitted with a connector to easily connect the light panel and the driver. Supplied with remote LED driver.

5 year warranty.

**Product Image:**



**Product Features:**


- Edge lit design provides superior lighting performance and uniform light output across the surface
- High transmission diffuser drastically reduces uncomfortable glare which can cause eye strain in well-lit offices
- Dimmable and CX colour exchange version available to set the desired light environment
- UGR (unified glare rating) - 19 - perfect for use in offices
- Heatsink design dissipates unwanted heat through rear of fitting, drastically reducing heat emitted through front and r for air conditioning
- 110-265V voltage range suitable for worldwide installation
- Dimmable (1-10V) and CX options also available
- IP44 from below – suitable for use in commercial kitchens, health care etc (recessed)
- Up to x3 longer life than triphosphor fluorescent
- Suitable for installation in 15 & 24mm T-bar ceilings
- May also be surface mounted or suspended
- Panel frame RAL9016 White
- High colour rendering index (Ra) 80 – ErP Compliant
- DALI options available, please call sales office for details
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty - see [www.auroralighting.com](http://www.auroralighting.com) for details

Versatile™ 30W 600 x 600mm ColourSwitching Dimmable Panel



**Product Specs:**

|                               |       |                        |             |
|-------------------------------|-------|------------------------|-------------|
| Technology                    | LED   | Input Voltage          | 220~240V AC |
| LED Chip                      | 3014  | Number of LEDs         | 240         |
| Positional Adjustment         | Fixed | Input Frequency        | 50/60HZ     |
| Lifetime L70 (hrs)            | 40000 | Power Factor           | 0.9         |
| Dimmable                      | No    | Luminaire Distribution | Direct      |
| Positional Adjustment         | Fixed | IP Rating              | IP44        |
| Fire Protection               | No    | SDCM                   | 4           |
| Operating Env. Temp. (Max) °C | 25°C  | Optic Material         | PS          |
| Length (mm)                   | 595   | Width (mm)             | 595         |
| Recess Depth (mm)             | 12    | Weight (Kg)            | 3.571       |

**Line Drawing**



**Polar Curve**



**SKU Table and Ordering:**

| SKU Code    | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|-------------|---------|--------|--------|-------------|------------|---------------|
| AU-LP102BSD | 30      | 6500   | 2125   | 71          | 120        | White         |

**Compliance & Approvals:**



**Accessories:**

| SKU Image | SKU Code  | Description                          |
|-----------|-----------|--------------------------------------|
|           | AU-CRM660 | 600 x 600mm Panel Recess Mount       |
|           | AU-SK100B | Panel Adjustable Suspension Kit      |
|           | AU-SM103B | 600 x 600 x 74mm Panel Surface Mount |

**Warranty:**

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.