

Product Description: Versitile™ 60W 1200 x 600mm Panel

SKU Code	Wattage	Colour	Lumens	Lumens/Watt
AU-LP103A/30	60	3000	5240	88
AU-LP103A/30EM	60	3000	5240	88
AU-LP103A/40	60	4000	5000	84
AU-LP103A/40EM	60	4000	5000	84

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- A range of edge-lit LED flat panels for office and commercial lighting
- Suitable for installation in 15 & 24mm T-bar ceilings
- Panel frame RAL9016 White
- May also be surface mounted or suspended
- All versions use optical polycarbonate for even light distribution
- IP44 from below when recessed mounted - suitable for use in commercial kitchens, clean rooms, healthcare and similar environments
- High colour rendering index (Ra) 80
- UGR (unified glare rating) - 19 - perfect for use in offices
- Life to 70% lumen maintenance (L70) - 40,000 hours
- DALI options available, please call sales office for details
- 5 Year Warranty - see [www.auroralighting.com](http://www.auroralighting.com) for details

## Product Specs:

Input Voltage	110~240V AC	Lifetime L70 (hrs)	50000hrs
Width (mm)	595	Length (mm)	1195
Weight (Kg)	9.533	Height (mm)	12

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.