

Product Description:

Versitile[™] 38W IP44 1200 x 300mm Panel

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-LP104B/30	38	3000	3600	95	120	White
AU-LP104B/30D	38	3000	3600	95	120	White
AU-LP104B/30DEM	38	3000	3600	95	120	White
AU-LP104B/30EM	38	3000	3600	95	120	White
AU-LP104B/40	38	4000	3900	103	120	White
AU-LP104B/40D	38	4000	3900	103	120	White
AU-LP104B/40DEM	38	4000	3900	103	120	White
AU-LP104B/40EM	38	4000	3900	103	120	White

Line Drawing	Polar Curve	Colour	

Feature & Benefits

- Edge lit design provides superior lighting performance and uniform light output across the surface
- High transmission diffuser drastically reduces uncomfortable glare which can cause eye strain in well-lit offices
- UGR (unified glare rating) 19 perfect for use in offices
- 110-265V voltage range suitable for worldwide installation
- IP44 from below suitable for use in commercial kitchens, health care etc (recessed)
- Panel frame RAL9016 White
- High colour rendering index (Ra) 80 - ErP Compliant
- Life to 70% lumen maintenance (L70) 40,000 hours
- Suitable for installation in 15 & 24mm T-bar ceilings

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	40000hrs
Length (mm)	1195
Height (mm)	12

Input Frequency	50/60HZ
IP Rating	IP44
Width (mm)	295
Weight (Kg)	4.531
Operating Temp. (Max) °C	25°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.