



Product Description: Versatile™ 40W CRI95 1200 x 300mm IP65 Non-Dimmable Panel


40W LED Light Panel with high Colour Rendering Index of 95 and R9 > 70. Fitted with prismatic diffuser for minimal glare as low as UGR16. Lightweight slim aluminium frame in RAL9016 white finish. IP rating of IP44 from the front of the panel and IP20 from the back. Suitable for installations in 15 and 24 mm T-bar ceilings. May also be surface mounted or suspended. Ideal for the use in healthcare applications where high precision tasks are performed. Fitted with a connector to easily connect the light panel and the driver. Supplied with remote LED driver.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-LP104CRI95AK/40	40	4000	3000	75	80	RAL9016

Line Drawing

Polar Curve

Colour



Feature & Benefits

- High CRI of 95 for premium quality of light
- Plain flat design to avoid dust gathering around the luminaire
- IP65 front and back – suitable for use in commercial kitchens, health care and similar environments
- L(70) at 50,000 hours lifetime
- 5 year warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC	Power Factor	0.9
IP Rating	IP65	Lifetime L70 (hrs)	50000hrs
Width (mm)	1195	Length (mm)	295
Height (mm)	9.5	Product Type	Panels
Operating Temp. (Min) °C	-40°C	Operating Temp. (Max) °C	85°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.