


Product Description: Versitile™ 60W 1200 x 600mm IP65 Dimmable Panel

Highly efficient award winning edge-lit dimmable LED light panels. Fitted with high transmission diffuser for minimal glare. Lightweight slim aluminium frame in RAL9016 White finish. IP rating of IP65 from front (Driver and connections IP20). Suitable for installations in 15 and 24mm T-bar ceilings. May also be surface mounted or suspended. Fitted with a connector to easily connect the light panel and the driver. Supplied with remote LED driver.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-LP105CAK/30	60	3000	5300	89	120	RAL9016
AU-LP105CAK/30EM	60	3000	5300	89	120	RAL9016
AU-LP105CAK/40	60	4000	5500	92	120	RAL9016
AU-LP105CAK/40EM	60	4000	5500	92	120	RAL9016



Feature & Benefits

- Edge lit design provides superior lighting performance and uniform light output across the surface
- High transmission diffuser drastically reduces uncomfortable glare which can cause eye strain in well-lit offices
- Dimmable and CX colour exchange version available to set the desired light environment
- UGR (unified glare rating) - 19 - perfect for use in offices
- Heatsink design dissipates unwanted heat through rear of fitting, drastically reducing heat emitted through front and rear for air conditioning
- 110-265V voltage range suitable for worldwide installation
- Dimmable (1-10V) and CX options also available
- IP65 front and back – suitable for use in commercial kitchens, health care and similar environments
- Up to x3 longer life than triphosphor fluorescent
- Suitable for installation in 15 & 24mm T-bar ceilings
- May also be surface mounted or suspended
- Panel frame RAL9016 White
- High colour rendering index (Ra) 80 – ErP Compliant
- DALI options available, please call sales office for details
- (L70) at a 50,000 hour lifetime
- 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	50000hrs	Width (mm)	595
Length (mm)	1195	Height (mm)	9.5
Product Type	Panels	Operating Temp. (Min) °C	-40°C
Operating Temp. (Max) °C	25°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.