


Product Description: Versitile™ 40W 1200 x 150mm Interconnectable Panel


Inter-connectable LED flat panel for continuous lighting schemes in applications for office and other commercial buildings. Complete solution including driver mounting box including driver and suspension cable. Also available in Dali.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-LP109AAK/40	40	4000	3500	88	120	White

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Interconnectable suspended LED flat panel for office and commercial lighting
- 1-10V dimmable
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	100~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	40000hrs	Width (mm)	150
Length (mm)	1200	Height (mm)	10
Product Type	Panels	Operating Temp. (Min) °C	25°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.