

Product Description:


Versitile™ 38W 622 x 622mm IP65 Dimmable Panel

Highly efficient award winning edge-lit dimmable Versitile™ LED light panel. Fitted with high transmission diffuser for minimal glare. Lightweight slim aluminium frame in RAL9016 White finish. IP rating of IP65 from front and back (Driver and connections IP20). Suitable for installations in 15 and 24mm T-bar ceilings. May also be surface mounted or suspended. Fitted with a connector to easily connect the light panel and the driver. Supplied with remote LED driver.


5 year warranty.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|----------------|---------|--------|--------|-------------|------------|---------------|-----------|
| AU-LP301C/30 | 38 | 3000 | 3600 | 95 | 120 | White | Dimmable |
| AU-LP301C/30EM | 38 | 3000 | 3600 | 95 | 120 | White | Emergency |
| AU-LP301C/40 | 38 | 4000 | 3900 | 103 | 120 | White | Dimmable |
| AU-LP301C/40EM | 38 | 4000 | 3900 | 103 | 120 | White | Emergency |

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Edge lit design provides superior light performance and uniformity ideal for offices and commercial lighting
- High transmission diffuser drastically reduces uncomfortable glare
- Heatsink rapidly dissipates heat through rear of fitting
- Dimmable and CX colour exchange version available to set the desired light environment
- IP65 front – suitable for use in commercial kitchens, health care and similar environments
- Suitable for installation in 15 & 24mm T-bar ceilings
- Panel frame RAL9016 White
- High colour rendering index (Ra) 80
- SDCM <4 providing consistent light colour quality
- DALI and Emergency options available
- (L70) at a 50,000 hour lifetime
- 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

| | | | |
|--------------------------|-------------|--------------------------|---------|
| Input Voltage | 220~240V AC | Input Frequency | 50/60HZ |
| Power Factor | 0.9 | IP Rating | IP65 |
| Lifetime L70 (hrs) | 50000hrs | Width (mm) | 622 |
| Length (mm) | 622 | Height (mm) | 9.5 |
| Product Type | Panels | Operating Temp. (Min) °C | -40°C |
| Operating Temp. (Max) °C | 85°C | | |

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.