

Product Description:

Aurora Compact fluorescent Pressed Steel low energy fire rated downlight. Pack includes: Compact fluorescent downlight with integral electronic ballast. Compact fluorescent lamp - 18W, 4000K. White bezel trim.

Product Image:



PLT-E 18W Fixed Fire Rated Downlight with Lamp

Product Features:

- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Compact fluorescent lamp - 4000K
- Compact fluorescent downlight with integral electronic ballast
- UK Patent GB2426321
- >45 Lumens per Watt output allows compliance with the Building Regulations Approved document L1A/B requiring the use of energy efficient luminaires in dwellings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Non-dimmable

Product Specs:

Input Voltage	220~240V AC	Dimmable	No
Overall Diameter (mm)	108	Length (mm)	140
Width (mm)	75	Recess Depth (mm)	155
Weight (Kg)	0.488		

SKU Table and Ordering:

SKU Code	Wattage	Colour
AU-LPF650	18	4000

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.