

Product Description: m10™ 10W IP65 Colour Xchange Downlight

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle
AU-M10CX	10	6400	650	65	40

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Rated to 30, 60 & 90 minute fire ceilings
- CX Colour Xchange - Warm white to Cool white colour temperature adjustment 2700K – 6400K
- Ideal for retail, residential and commercial applications
- AU-M10CX – full colour temperature adjustment and dimming functions
- AU-M10SD – can be switched between 2700 / 4000 / 6400K with a standard light switch
- Twist&Lock™ IP65 Interchangeable bezels - sold separately
- BS EN 1365-2:2000 (Fire resistance)
- BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics)
- BS EN 13141-1:2004 (Air leakage)
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty – see [www.auroralighting.com](http://www.auroralighting.com) for details

## Product Specs:

Input Voltage	110~240V AC	Input Frequency	50/50HZ
IP Rating	IP65	Lifetime L70 (hrs)	40000hrs
Width (mm)	88	Length (mm)	83
Overall Diameter (mm)	88	Weight (Kg)	0.340
Height (mm)	83	Cutout Diameter (mm)	65-72

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.