

Product Description: m10™ 15W IP65 RGB Fire Rated Downlight

Fixed, integrated, fire rated 15W RGB LED downlight with new improved design featuring enhanced thermal management, integrated IC cap and improved efficacy. Requires 12V DC constant voltage LED driver (not included). Interchangeable bezels available in White, Matt White, Polished Chrome and Satin Nickel. Two lens options: 40° and 60° with 40° fitted as standard. Rated to 30, 60 and 90 minute fire ceilings. Complies with BS EN 1365-2: 2014 (fire resistance), BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics), BS EN 13141-1:2400 (Air leakage).

SKU Code	Wattage	Beam Angle	SKU Type
AU-M10RGBA	15	40	Non Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- EN 1365-2: 2014 (fire resistance)
- BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (Acoustics)

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.6
Lifetime L70 (hrs)	40000hrs
Weight (Kg)	0.368
Cutout Diameter (mm)	65-72

Input Frequency	50/60HZ
IP Rating	IP65
Overall Diameter (mm)	88
Height (mm)	71
Operating Temp. (Max) °C	25°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.