

## Product Description: 21W COB Module

Fixed 21W High Power LED Module. Simply twist and lock module and bezel together. Dimmable with suitable remote LED driver (sold separately). Interchangeable bezels available as fixed and adjustable in White, Matt White, Polished Chrome and Satin Nickel. Baffle accessories available. Optional interchangeable lenses available separately in 36° and 60°.

| SKU Code      | Wattage | Colour | Lumens | Lumens/Watt | Finish Colour | SKU Type |
|---------------|---------|--------|--------|-------------|---------------|----------|
| AU-MD10031/30 | 21      | 3000   | 1350   | 65          | White         | Dimmable |
| AU-MD10031/40 | 21      | 4000   | 1450   | 70          | White         | Dimmable |

## Line Drawing

## Polar Curve

## Colour

## Feature & Benefits

- International Design Registration No. DM/080 178
- High power and COB LED modules and bezels
- Simply twist and lock module and bezel together
- Fixed bezels with modules are IP65 rated
- Baffle accessories available
- Separate driver required
- Dimmable with suitable remote LED driver (sold separately)
- High colour rendering index (Ra) 84
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty - see [www.auroralighting.com](http://www.auroralighting.com) for details

## Product Specs:

|                          |             |
|--------------------------|-------------|
| Input Voltage            | 220~240V DC |
| Power Factor             | 0.9         |
| Lifetime L70 (hrs)       | 40000hrs    |
| Overall Diameter (mm)    | 76          |
| Height (mm)              | 80          |
| Operating Temp. (Max) °C | 25°C        |

|                 |            |
|-----------------|------------|
| Input Frequency | 50/60HZ    |
| IP Rating       | IP20       |
| Length (mm)     | 80         |
| Weight (Kg)     | 0.225      |
| Product Type    | Downlights |

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.