


Product Description: mPro™ Adjustable IP65 Dimmable Fire Rated Downlight


Adjustable, integrated, fire rated 6W LED downlight with unique convertible design to fit ceiling voids as shallow as 56mm. Incorporated miniaturised NanoDrive™ power supply. Available in 3000K and 4000K, mPro™ delivers up to 107lm/W making it the most efficient fire rated downlight on the market. Interchangeable bezels available in White, Matt White, Polished Chrome and Satin Nickel. FastRFix™ rapid install system connector included for faster installation.
PLEASE NOTE: Any purchases before 01/01/2021 has a 5 Year Warranty

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-MPRO2AMW/30	6	3000	610	102	60	Matt White	Triac Dimmable
AU-MPRO2AMW/40	6	4000	640	107	60	Matt White	Triac Dimmable
AU-MPRO2APC/30	6	3000	610	102	60	Polished Chrome	Triac Dimmable
AU-MPRO2APC/40	6	4000	640	107	60	Polished Chrome	Triac Dimmable
AU-MPRO2ASN/30	6	3000	610	102	60	Satin Nickel	Triac Dimmable
AU-MPRO2ASN/40	6	4000	640	107	60	Satin Nickel	Triac Dimmable
AU-MPRO2AW/30	6	3000	610	102	60	White	Triac Dimmable
AU-MPRO2AW/40	6	4000	640	107	60	White	Triac Dimmable


Line Drawing




Polar Curve



Colour



Matt White | Polished Chrome | Satin Nickel



White

Feature & Benefits

- LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- Convertible design to fit ceiling voids as shallow as 56mm
- Delivering up to 107lm/W
- IP65 rated
- FastRFix™ rapid install system connector included
- 60° beam angle for uniform light distribution
- Fibre based insulation coverable - up to 300mm
- Fire tested with solid timber, ijoist and metal web joists
- 7 Year Warranty
- PLEASE NOTE: When used with blown insulation, this product has a 5 Year Warranty at L70 40,000hrs
- PLEASE NOTE: Purchases before 2021 has a 5 Year Warranty

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.80
Lifetime L70 (hrs)	70000hrs
Weight (Kg)	0.529
Product Type	Downlights,Fire-Rated Downlight
Operating Temp. (Min) °C	-20°C

Input Frequency	50/50HZ
IP Rating	IP65
Overall Diameter (mm)	98
Height (mm)	100
Cutout Diameter (mm)	85-85
Operating Temp. (Max) °C	45°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 7 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.