



Product Description:

T8 30W 1800mm

SKU Code	Colour	Lumens	Lumens/Watt	Wattage
AU-PT818030CL/40	4000	2655	89	30
Line Drawing	Polar Curve		Colour	

Feature & Benefits

- Community Registered Design 001917592
- Integrated passive infra-red
- 140 degrees area of detection
- 5-8m detection range
- Potentiometers on the PIR for adjustment of time delay and brightness
- Time can be set from 30 seconds to 30 minutes
- Brightness can be set to 0, 10, 20, 30 or 40%
- After the last movement is detected the tube will remain fully lit for the time delay period. The lamp will then dim to the set brightness level
- Rotatable end caps
- 3 Rows of SMD LEDs

- Aluminium back for heatsinking of LEDs
- Impact resistant clear or frosted polycarbonate diffuser
- High power factor >0.90
- Suitable for use at -20° to +40°C
- 1kV surge protection
- Beam 120°
- Voltage range 110-265V
- Life to 70% lumen maintenance - 40,000 hours

Product Specs:

Input Voltage	100~265V AC/DC	Overall Diameter (mm)	28
Lamp Base	G13	Lamp Type	PAR38
Weight (Kg)	0.6	Lifetime Hours	40000hrs

Compliance & Approvals:













This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.