




Product Description:

R6™CWS Fixed 4-8W Colour & Wattage Switchable Baffled Fire Rated Downlight


With the installer and wholesaler in mind, Aurora introduces the R6™CWS. This R6™CWS is Aurora's baffled colour and wattage switchable fire rated downlight, supplied with an AMP connector applied to a remote detachable driver with a loop in/loop out terminal block. Colour switch is located on the back of the fitting and the wattage switch can be found on the remote driver. This baffled option is fantastic to help reduce glare. Product comes complete with a polycarbonate white bezel (polished chrome, satin nickel and matt black bezels sold separately).

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-R6CWSBF	4	3000K	260	55	White	Dimmable
AU-R6CWSBF	4	4000K	300	55	White	Dimmable
AU-R6CWSBF	4	5700K	290	55	White	Dimmable
AU-R6CWSBF	6	3000K	390	55	White	Dimmable
AU-R6CWSBF	6	4000K	450	55	White	Dimmable
AU-R6CWSBF	6	5700K	420	55	White	Dimmable
AU-R6CWSBF	8	3000K	470	55	White	Dimmable
AU-R6CWSBF	8	4000K	560	55	White	Dimmable
AU-R6CWSBF	8	5700K	500	55	White	Dimmable


Line Drawing




Polar Curve



4W - 4000K




6W - 4000K



8W - 4000K

Colour



White

Feature & Benefits

- Baffled design to reduce direct glare
- Colour temperature can be switched between 3000K, 4000K and 5700K
- Wattage switchable between 4W, 6W and 8W
- Supplied with detachable remote driver
- Supplied with white IP65 polycarbonate bezel
- Insulation coverable
- Patented fire rated downlight without intumescent
- Select colour temperature and wattage prior to installation
- Fire, acoustic and air leakage rated
- Tested in 30, 60 and 90 minute solid timber joist, plus 30 minute i-joists and metal web joist
- 55° beam angle
- L70 40,000hrs
- Triac dimmable as standard
- IP65 Polycarbonate Polished Chrome, Satin Nickel and Matt Black bezel options
- 5 Year Warranty

Product Specs:

Input Voltage	220~240V
Power Factor	0.85
Lifetime L70 (hrs)	50000hrs
Weight (Kg)	.24
Product Type	Fire-Rated Downlight
Operating Temp. (Min) °C	-20°C
Insulated Covered Operating Temp. (Min) °C	-20+°C

Input Frequency	50/50HZ
IP Rating	IP65
Overall Diameter (mm)	88
Height (mm)	75
Cutout Diameter (mm)	75-75
Operating Temp. (Max) °C	45°C
Insulated Covered Operating Temp. (Max) °C	45+°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.