

Product Description:

2 x 20W Adjustable Rectangular Twin Spotlight

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-RS212W/40	40	4000	4000	100	24	White
Line Drawing		Polar Curve		Colou	ır	
Feature & Benefits						
 Recessed spotlight incorporating high power COB LED light engine and integrated driver Suitable for retail / commercial applications consisting of single, twin, rounded and squared bezels 2000 Lumen or 3000 lumen packages available 	(3000 lu • Active c	(24°) beam distribution	beam refle accessories • Single and	s°) and wide (33°) ctors available as s (no tools required) three circuit track ersions also available able	• 5 Year Warra	,000 hour lifetime nty - see ghting.com for

Product Specs:

Input Voltage	240~240V AC	Input Frequency	50/60HZ
Power Factor	0.95	IP Rating	IP20
Lifetime L70 (hrs)	50000hrs	Width (mm)	208
Length (mm)	400	Overall Diameter (mm)	142
Cutout Length (mm)	370	Cutout Width (mm)	190
Projection (mm)	131	Height (mm)	174

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.