

**Product Features:**

- Patented Self Monitoring technology (Pat.No.GB2371424)
- Fully dimmable with resistive & inductive dimmers
- Auto-reset thermal protection
- Short circuit and overload protection
- 1.0kV SURGE PROTECTION – EN 61547
- Suitable for use in commercial or light industrial installations
- Loop-in, loop-out primary wiring terminals
- No junction box required
- Intergrated earth terminals for earth continuity
- Pre-wired with 30cm LV cable MR16 lampholder and lamp retaining clip
- Safety compliance – EN 61347
- EMC compliance – EN 55015, EN 61000, EN 61547
- 10 Year guarantee
- NOTE: MAX. CABLE LENGTH FROM TRANSFORMER TO THE FURTHEST LAMP IS 2M
- MONITORING LED STATUS
- ON – Normal operation
- OFF – Out of order (check mains power supply)
- SLOW FLASHING – Short circuit on transformer output
- RAPID FLASHING – Overload condition on transformer output

**Product Image:**



20-60W/VA Selbstüberwachender elektronischer Transformator

**Product Specs:**

Input Voltage	220~250V AC	Width (mm)	40
Length (mm)	132	Weight (Kg)	0.105
Case Cover Colour	Red	Case Material	Polycarbonate

**SKU Table and Ordering:**

SKU Code	Lumens/Watt
AU-SM60T	0

**Compliance & Approvals:**



**Warranty:**

1 Jahr. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.