

Product Description: IP65 1 x Signage Module

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle
AU-SN112CW	2	7000	165	83	160

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 High Output LED Signage modules to replace fluorescent tubes in box signs, advertisement boards, light boxes etc.
- Improved uniformity, reduced energy and maintenance costs over fluorescent tubes
- Can be cut between modules for ease of installation in new or retrofit signs
- 12V DC low voltage input
- SMD3535 LEDs
- Pre-drilled mounting holes and industrial grade adhesive backing
- Maximum number of modules per circuit is 20pcs
- For runs over 20 modules, circuits should be connected in parallel
- Supplied in packs of 20 modules
- Dimmable up to 11m/44 modules with AU-LEDD9012 dimmable LED driver & AU-DSPLED 1-10V dimmer
- (L70) at a 25,000 hour lifetime
- 3 years warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	12~12V DC	IP Rating	IP65
Lifetime L70 (hrs)	25000hrs	Width (mm)	35
Length (mm)	52	Weight (Kg)	0.259
Height (mm)	8	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	60°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.