

Product Description:

IP68 Single Colour Flexible Strip

12V DC Single Colour Flexible LED Strip Light. IP68. Single colour flexible LED strip. Requires 12V DC Constant Voltage LED driver.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle
AU-ST100IP/CW	4.8	6400	260	55	120
AU-ST100IP/WW	4.8	3500	190	40	120

Line Drawing Polar Curve Colour

Feature & Benefits

- Single colour flexible LED strip
- Ideal for fast installation into many applications including signs, displays and pelmets
- IP68 rating allows use in marine / boat applications
- Any joints / terminations are maximum IP65
- Cut point every 50mm
- 16mm between LEDs (SMD3528)
- Beam angle 120°
- Voltage drop of 2V per 5 metres
- Maximum length of run 10m
- Copper track for effective heat dissipation and long life
- Requires 12V DC Constant Voltage LED driver
- Dimmable up to 18m with AU-LEDD9012 dimmable LED driver & AU-DSPLED 1-10V dimmer
- Very low power consumption 4.8W per metre
- Please order to the nearest metre. Prices per metre (Reel length 10m)
- 3 Year Warranty see www.auroralighting.com for details

Product Specs:

Input Voltage	12~12V DC	IP Rating	IP68
Lifetime L70 (hrs)	25000hrs	Width (mm)	10
Length (mm)	5000	Weight (Kg)	0.567
Height (mm)	5	Product Type	LED Strip

Compliance & Approvals:











Warranty

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.