

Product Description: IP68 Single Colour Flexible Strip

Aurora 24V DC LED IP68 Round Single Colour Flexible LED Strip Light.  
Connection kit will work with AU-ST110CK.

SKU Code	Wattage	Beam Angle
AU-ST102BLU	2.5	120
AU-ST102GRN	2.5	120
AU-ST102RD	2.5	120
AU-ST102W	2.5	120
AU-ST102WW	2.5	120

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- IP68 Low voltage single colour LED flexible strip light
- Suitable for building features, stair/bar edging, floor marking, signage, marine and outdoor lighting
- IP68 Rating allows use in marine/boat applications
- Requires 24V DC constant voltage LED driver
- Cut point every 6 LEDs
- For runs over 20m individual lengths should be connected in parallel\*
- Very low power consumption - 2.5W per metre
- High flexibility - minimum bend radius 2cm
- IP68 accessories and connector kits available
- Non-dimmable
- Please order to the nearest metre (reel length 20m)

## Product Specs:

Input Voltage	24~24V DC	IP Rating	IP68
Lifetime L70 (hrs)	30000hrs	Overall Diameter (mm)	55
Weight (Kg)	0.89	Projection (mm)	5.5

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.