

Product Description:

Versitile[™] 40W 1200 x 300mm Suspended Dimmable Panel

Range of suspended LED flat panels with an efficacy of 88lm/W ideal for office and other commercial applications. Driver mounting box with driver included. Available with alternative suspension methods and in Dali.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Finish Colour	SKU Type
AU-SU101B/30	40	3000	3300	83	White	Dimmable
AU-SU101B/30D	40	3000	3300	83	White	DALI Dimmable
AU-SU101B/40	40	4000	3500	88	White	Dimmable
AU-SU101B/40D	40	4000	3500	88	White	DALI Dimmable

Line Drawing	Polar Curve	Colour
Feature & Benefits		
 Suspended LED flat panel for office and commercial lighting 70% down and 30% upward light distribution 	 Optical polycarbonate for even light distribution 1-10V dimmable 	 (L70) at a 40,000 hour lifetime 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	110~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	40000hrs	Width (mm)	295
Length (mm)	1195	Weight (Kg)	5.048
Height (mm)	15	Product Type	Panels
Operating Temp. (Max) °C	25°C		

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.