



Product Description: 220-240V 26W 200mmx300mm Recessed LED Troffer

Direct/Indirect Low glare centre diffused K19 high efficiency precise optical control Soft Tone Troffer with high LED performance 115Lm/w L70 50,000 hrs. T-Bar grid ceiling ideal for commercial, hospitality, education applications.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-TFL12304AK/40	26	4000	3000	116	90	RAL9016	Non Dimmable
AU-TFL12304DAK/40	26	4000	3000	116	90	RAL9016	DALI Dimmable

Line Drawing

Polar Curve


Colour

Feature & Benefits

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP40
Lifetime L70 (hrs)	50000hrs	Width (mm)	295
Length (mm)	1195	Height (mm)	100
Operating Temp. (Min) °C	0°C	Operating Temp. (Max) °C	25°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.