

Product Description: 20W Adjustable Single Circuit Spotlight

| SKU Code        | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|-----------------|---------|--------|--------|-------------|------------|---------------|
| AU-TMSS413SS/30 | 20      | 3000   | 2000   | 100         | 24         | Satin Silver  |
| AU-TMSS413SS/40 | 20      | 4000   | 2000   | 100         | 24         | Satin Silver  |
| AU-TMSS413W/30  | 20      | 3000   | 2000   | 100         | 24         | Matt White    |
| AU-TMSS413W/40  | 20      | 4000   | 2000   | 100         | 24         | Matt White    |

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Single circuit LED track spotlight incorporating high power COB LED light engine and integrated LED driver
- Track lighting offers maximum flexibility for retail / commercial applications where light sources need to be moved to account for changes in displays
- 2000 lumen or 3000 lumen packages available
- Direct replacement for 35W HID (3000 lumen package)
- Active cooling
- Medium beam distribution as standard
- Narrow and wide distributions available as accessories (no tools required)
- Active cooling
- ErP - High colour rendering index (Ra) >80
- Non-dimmable
- (L90) at a 50,000 hour lifetime
- 5 Year Warranty - see [www.auroralighting.com](http://www.auroralighting.com) for details

## Product Specs:

|                       |             |                    |          |
|-----------------------|-------------|--------------------|----------|
| Input Voltage         | 240~240V AC | Input Frequency    | 50/60HZ  |
| Power Factor          | .9          | Lifetime L70 (hrs) | 50000hrs |
| Width (mm)            | 142         | Length (mm)        | 223      |
| Overall Diameter (mm) | 142         | Weight (Kg)        | 1.119    |
| Height (mm)           | 226         |                    |          |

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.