

Product Description:

Universal[™] Adjustable Fire Rated Downlight

The only Fire Rated Downlight that we know of that is suitable for ANY Bulb technology (halogen, CFL, or LED), along with allowing insulation material to be placed on top of the fitting guard. It also comes fitted with a GU10 lampholder and includes an MR16 Lampholder for convenient choice of bulb type. A truly great product which solves all your specification and installation needs in 1 fell swoop. Lamps not included.

SKU Code	W Matt White C Polished Chrome N Satin Nickel	
AU-UNIF782MW		
AU-UNIF782PC		
AU-UNIF782SN		
AU-UNIF782W		

Line Drawing Polar Curve	Colour
--------------------------	--------

Feature & Benefits

- Registered Community Design -001926429 European Patent -EP1726873B1 UK Patent -2426321B
- Universal fire rated downlight allows the use of halogen, CFL and LED lamps
- Increased ventilation slots allow heat from all lamp types to be effectively dissipated
- Fitted insulation cover cap allows the downlights to be IC rated - covered with insulation material if necessary. Downlight insulation guard not required
- Tested in 30, 60 & 90 minute fire rated ceilings. 2 year guaranteee
- Supplied with GU10 lampholder fitted and optional MR16 lampholder for freedom of lamp choice
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation

Product Specs:

Input Voltage		Lamp Base	GU10
Width (mm)	135	Overall Diameter (mm)	95
Weight (Kg)	0.343	Height (mm)	134
Cutout Diameter (mm)	85-		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.