



**Product Description:** Universal™ Fire Rated Downlight with 6W Lamp

This Long form Fire rated Downlight is suitable for ANY Bulb technology (halogen, CFL, or LED), whether it's a long or standard length Lamp. Additionally you can lay insulation material on top of the fitting guard. It also comes fitted with a GU10 lamp holder and includes an MR16 Lamp holder for convenient choice of bulb type. A truly great product which solves all your specification and installation needs in 1 fell swoop. Choose /30 for Warm White and /40 for Cool White lamps.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-UNIF851MW/30	6	3000	400	67	40	Matt White
AU-UNIF851MW/40	6	4000	410	69	40	Matt White
AU-UNIF851PC/30	6	3000	400	67	40	Polished Chrome
AU-UNIF851PC/40	6	4000	410	69	40	Polished Chrome
AU-UNIF851SN/30	6	3000	400	67	40	Satin Nickel
AU-UNIF851SN/40	6	4000	410	69	40	Satin Nickel
AU-UNIF851W/30	6	3000	400	67	40	White
AU-UNIF851W/40	6	4000	410	69	40	White



### Product Features:

- Universal fire rated downlight + Aone 6W Warm White Non-Dimmable LED Lamp 50W Equivalent (450 Lumens)
- Increased ventilation slots allow heat from all lamp types to be effectively dissipated
- Fitted insulation cover cap allows the downlights to be IC rated - covered with insulation material if necessary. Downlight insulation guard not required
- Supplied with GU10 lampholder fitted and optional MR16 lampholder for flexibility of lamp choice
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire. Tested in 30, 60 & 90 minute fire rated ceilings

### Product Specs:

Input Voltage	12~240V AC	Input Frequency	50/60HZ
Lamp Base	GU10	Width (mm)	135
Overall Diameter (mm)	90	Weight (Kg)	0.265
Cutout Diameter (mm)	75		

### Compliance & Approvals:



### Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.