



**Product Description:** UtiliteXL™ 14W-24W IP65 Colour & Wattage Switchable Wall Pack

Designed to last in a tough environment, the UtiliteXL™ wall pack with cast aluminium base and polycarbonate diffuser is available in standard, photocell and emergency versions with black housing.

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-WP103CWS	14	3000K	1700	120	Black	Non Dimmable
AU-WP103CWS	14	4000K	1850	120	Black	Non Dimmable
AU-WP103CWS	14	6500K	1700	120	Black	Non Dimmable
AU-WP103CWS	17	3000K	2100	120	Black	Non Dimmable
AU-WP103CWS	17	4000K	2250	120	Black	Non Dimmable
AU-WP103CWS	17	6500K	2100	120	Black	Non Dimmable
AU-WP103CWS	21	3000K	2520	120	Black	Non Dimmable
AU-WP103CWS	21	4000K	2750	120	Black	Non Dimmable
AU-WP103CWS	21	6500K	2520	120	Black	Non Dimmable
AU-WP103CWSPH	14	3000K	1700	120	Black	Photocell
AU-WP103CWSPH	14	4000K	1850	120	Black	Photocell
AU-WP103CWSPH	14	6500K	1700	120	Black	Photocell
AU-WP103CWSPH	17	3000K	2100	120	Black	Photocell
AU-WP103CWSPH	17	4000K	2250	120	Black	Photocell
AU-WP103CWSPH	17	6500K	2100	120	Black	Photocell
AU-WP103CWSPH	21	3000K	2520	120	Black	Photocell
AU-WP103CWSPH	21	4000K	2750	120	Black	Photocell
AU-WP103CWSPH	21	6500K	2520	120	Black	Photocell

Line Drawing

Polar Curve

Colour

### Feature & Benefits

- Colour switchable between 3000K, 4000K and 6500K
- Side and rear entry
- -20 - +45° ambient operating temperature
- 5 Year Warranty
- Wattage switchable between 14/17/21/24W
- IP65 rated
- Emergency pack available to purchase separately (AU-EM4)
- 3 year on-site warranty (registration required) \*Terms and conditions apply
- Polycarbonate body and diffuser
- IK10 rated

### Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	50000hrs	IK Rating	IK10
Lamp Base	None	Width (mm)	162
Length (mm)	309	Weight (Kg)	1.5
Projection (mm)	115	Height (mm)	217
Product Type	Wall Lights	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	45°C		

### Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.