

**Product Description:**

Gama de baliza LED de bajo voltaje 316 acero inoxidable IP68. Resistente a la corrosión para uso en áreas costeras. LED no reemplazables. Ideal para usar en plataformas, patios, pasillos, piscinas, estanques, etc. Equipado con un cable de goma para la conexión a un controlador LED. 1 ao de garantía

**Product Image:**




Baliza 3W IP69

**Product Features:**

**Product Specs:**

Technology	LED	Input Voltage	~V DC
LED Chip	Alta potencia	Number of LEDs	3
Positional Adjustment	Fijo	Lifetime L70 (hrs)	10000
Dimmable	No	Positional Adjustment	Fijo
IP Rating	IP68	Fire Protection	No
Overall Diameter (mm)	76	Length (mm)	47
Cutout Diameter (mm)	65	Recess Depth (mm)	55
Weight (Kg)	0.625		

**Line Drawing**




**SKU Table and Ordering:**

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-WU300/30	3	3000	300	100	45	Acero Inoxidable
AU-WU300/60	3	5600	300	100	45	Acero Inoxidable

**Compliance & Approvals:**



**Accessories:**

SKU Image	SKU Code	Description
	AU-MS65	Tubo prolongador para montaje de downlight , diámetro: 65 mm

**Warranty:**

This product has a warranty period of 1 ao. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.