Product Description: Isopro Adjustable 5W GU10 Coverable Recessed Downlight Pack

The Isopro range is designed to ensure a perfect airtightness of the ceilings in all environments and whatever the constraints. Thanks to its standard diameter flush-mounting can, the Isopro can be installed in place of conventional downlights and can be easily connected. Available with an ICE™ 5W LED lamp for maximum energy savings.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-AL120SN/30	5	3000	500	100	60	Satin Nickel	Non Dimmable
EN-AL120SN/40	5	4000	520	104	60	Satin Nickel	Non Dimmable
EN-AL120W/30	5	3000	500	100	60	White	Non Dimmable
EN-AL120W/40	5	4000	520	104	60	White	Non Dimmable
EN-AL120WCP10/30	5	3000	500	100	60	White	Non Dimmable
EN-AL120WCP10/40	5	4000	520	104	60	White	Non Dimmable

Line Drawing



Polar Curve



Colour



Satin Nickel White

Feature & Benefits

- Recessed airtight LED downlight - Building regulation compliant
- Suitable for all types of insulation materials (fibre / blown / sprayed) and vapour barrier tarpaulin
- Supplied with a quick-release and plug-in terminals connector
- Low installation depth thanks to its flexible bracket
- 30, 60 & 90min fire resistant in fireproof ceilings
- Supplied with 5W ICE™ GU10 lamp
- White & satin nickel finish options
- 2 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.5	IP Rating	IP20
Lifetime L70 (hrs)	25000hrs	Lamp Base	GU10
Overall Diameter (mm)	90	Height (mm)	100
Product Type	Downlights,Fire-Rated Downlight	Cutout Diameter (mm)	85-85

Compliance & Approvals:

Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.