




**Product Description:** LinearPac<sup>™</sup> 1200mm 20W IP65 Anti-Corrosive


The IP65 LinearPac<sup>™</sup> LED anti-corrosive provides up to 50% energy savings compared to traditional fluorescent. A highly efficient solution for both interior and exterior applications, it is designed for car parks, service areas, warehouses or retail environments.  
PLEASE NOTE: Any purchases before 01/01/2021 has a 3 Year Warranty

| SKU Code         | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type     |
|------------------|---------|--------|--------|-------------|------------|---------------|--------------|
| EN-ANT1217B/40   | 20      | 4000   | 2400   | 120         | 120        | Grey          | Non Dimmable |
| EN-ANT1217BEM/40 | 20      | 4000   | 2000   | 100         | 120        | Grey          | Emergency    |

**Line Drawing**



**Polar Curve**



**Colour**



Grey


## Feature & Benefits

- IP65 vandal resistant polycarbonate body and diffuser
- Efficacy of 120lm/W
- Anti-tamper stainless steel clips supplied as standard
- Clip in gear tray for ease of installation and maintenance
- Multiple drill-out conduit entry points end and rear for quick and easy installation
- Supplied with 2 x IP rated cable glands
- Microwave sensor detection range up to 14 metres
- Adjustable light detector from 2-50 lux
- Adjustable hold time 5 seconds to 15 minutes
- IK08 impact rating
- 1.0kV surge protection
- SEAI: EN-ANT1217B/40 - LIG84992
- 5 Year Warranty
- PLEASE NOTE: Any purchase made before 01/01/2021 has a 3 Year Warranty

## Product Specs:

|                          |             |                          |         |
|--------------------------|-------------|--------------------------|---------|
| Input Voltage            | 220~240V AC | Input Frequency          | 50/60HZ |
| Power Factor             | 0.90        | IP Rating                | IP65    |
| Lifetime L70 (hrs)       | 50000hrs    | IK Rating                | IK08    |
| Lamp Base                | None        | Width (mm)               | 85      |
| Length (mm)              | 1270        | Weight (Kg)              | 1.387   |
| Height (mm)              | 80          | Product Type             | Linears |
| Operating Temp. (Min) °C | -20°C       | Operating Temp. (Max) °C | 40°C    |

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.