



Product Description:

LinearPac™ 1200mm 36W IP65 Polycarbonate LED Anti-Corrosive

The IP65 LinearPac<sup>™</sup> LED anti-corrosive is an ideal solution for both interior and exterior applications, allowing for an energy reduction compared to traditional linear fluorescent fittings. Popular for car parks, service areas, warehouses or retail applications, LinearPac creates the needed lighting levels while providing the energy savings desired.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-ANT1236/40	36	4000	3300	92	120	Grey	Non Dimmable
EN-ANT1236/40EM	36	4000	3300	92	120	Grey	Emergency
EN-ANT1236/40MS	36	4000	3300	92	120	Grey	Microwave
EN-ANT1236/60	36	6000	3600	100	120	Grey	Non Dimmable
EN-ANT1236/60EM	36	6000	3600	100	120	Grey	Emergency
EN-ANT1236/60MS	36	6000	3600	100	120	Grey	Microwave

Line Drawing Polar Curve Colour

## Feature & Benefits

- IP65 vandal resistant polycarbonate body and diffuser
- Efficacy of up to 100 lm/W
- Anti-tamper stainless steel clips supplied as standard
- Diffuser permanently attached by two clips for ease of installation
- Gear tray restraints for ease of installation and maintenance
- Through cable wiring with multiple drill-out conduit entry points for quick and easy installation
- Microwave sensor detection range up to 12 metres
- Adjustable light detector from 5-50 lux
- Adjustable hold time 5 seconds to 30 minutes
- IK08 impact rating
- 1.5kV surge protection

## **Product Specs:**

Input Voltage	100~240V AC		
Power Factor	0.95		
Lifetime L70 (hrs)	40000hrs		
Width (mm)	110		
Weight (Kg)	1.971		
Product Type	Linears		
Operating Temp. (Max) °C	70°C		

Input Frequency	50/60HZ
IP Rating	IP65
IK Rating	IK08
Length (mm)	1260
Height (mm)	85
Operating Temp. (Min) °C	-20°C

## Compliance & Approvals:

















This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.