





Product Description:

BatPac™ Colour Switchable 1200mm 20W Batten

Introducing BatPac<sup>TM</sup> CS. This product is a colour switchable LED batten that provides the direct replacements for single or twin fittings in size and output. Can also be surface mounted or suspended.

Colour can be switched between 3000K (2500lm), 4000K (2600lm) and 6300K (2500lm).

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
EN-BA1222CCT	20	3000K	2500	120	White	Non Dimmable
EN-BA1222CCT	20	4000K	2600	120	White	Non Dimmable
EN-BA1222CCT	20	6300K	2500	120	White	Non Dimmable
EN-BA1222CCTEM	20	3000K	2300	120	White	Emergency
EN-BA1222CCTEM	20	4000K	2600	120	White	Emergency
EN-BA1222CCTEM	20	6300K	2500	120	White	Emergency

Line Drawing Polar Curve Colour

## Feature & Benefits

- Colour switchable between 3000K, 4000K and 6300K
- Lumen value at 3000K is 2300lm
- Lumen value at 4000K is 2600lm
- Lumen value at 6300K is 2500lm
- Updated design with a push clip release mechanism
- Hinged gear tray and clip-in gear tray for fast installation
- Opal polycarbonate diffuser
- IK08 rated impact resistance
- Knockouts for cable entry on both ends
- Push-fit terminals
- Multiple BESA mounting points
- Adjustable light detector from 2-50 lux for microwave option
- Adjustable hold time of 5secs to 30mins for microwave option
- Can be surface mounted or suspended
- 5 Year Warranty

## **Product Specs:**

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	50000hrs
Lamp Base	Other
Length (mm)	1170
Height (mm)	71
Operating Temp. (Min) °C	-20°C

Input Frequency	50/60HZ
IP Rating	IP20
IK Rating	IK08
Width (mm)	61
Weight (Kg)	1.272
Product Type	Linears
Operating Temp. (Max) °C	45°C

## Compliance & Approvals:





























This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.