



Product Description: UtiliteDrum[™] 18W Polycarbonate IP65 Square Drum Bulkhead



Drum bulkhead fittings are the trusted workhorse commonly found in many installations. For years this traditional bulkhead has been fitted globally with energy consuming fluorescent lamps. With the UtiliteDrum[™] range, you can now upgrade to maintenance free, high efficiency LED alternatives without worrying about changing the look of existing installation. Available in round or square in both black and white with emergency and microwave versions.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-BH18SBLK/40	18	4000	1300	73	120	Black	Non Dimmable
EN-BH18SBLK/40EM	20	4000	1300	65	120	Black	Emergency
EN-BH18SBLK/40EMMS	20	4000	1300	65	120	Black	Emergency Microwave
EN-BH18SBLK/40MS	18	4000	1300	73	120	Black	Microwave
EN-BH18SW/40	18	4000	1300	73	120	White	Non Dimmable
EN-BH18SW/40EM	20	4000	1300	65	120	White	Emergency
EN-BH18SW/40EMMS	20	4000	1300	65	120	White	Emergency Microwave
EN-BH18SW/40MS	18	4000	1300	73	120	White	Microwave

Line Drawing

Polar Curve

Colour



Black

White

Feature & Benefits

- IP65 polycarbonate LED bulkhead
- Life not affected by frequent switching
- Tough IK10 polycarbonate body and diffuser
- Opal diffuser evenly diffuses light and eliminates LED hot spots
- Wall or ceiling mounting - accessories included
- 20mm conduit side entries
- Emergency and microwave options available
- Adjustable hold time 5 seconds to 30 minutes
- Adjustable light detector from 2-50 lux
- 1.5kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	180~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	25000hrs	IK Rating	IK10
Lamp Base	None	Width (mm)	255
Length (mm)	255	Weight (Kg)	0.845
Projection (mm)	95	Height (mm)	95
Product Type	Bulkheads	Operating Temp. (Min) °C	-25°C
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.