



**Product Description:** Orbital<sup>™</sup> 25W Polycarbonate IP66 Round Bulkhead


The IP66 Orbital<sup>™</sup> bulkhead range is simple yet perfect for bulkhead applications. Engineered with a tough polycarbonate body and opal diffuser for even light output with no LED hot spots, all versions and accessories are impact resistant and designed to last. Available in two wattages, white and black housing, interchangeable eyelid bezels, emergency and microwave options. This range ticks all the boxes for any installation. Life not affected by frequent switching e.g. when used with occupancy controls.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-BH25BLK/40	25	4000	1800	72	120	Black	Non Dimmable
EN-BH25BLK/40EM	27	4000	1800	67	120	Black	Emergency
EN-BH25BLK/40EMMS	27	4000	1800	67	120	Black	Emergency Microwave
EN-BH25BLK/40MS	25	4000	1800	72	120	Black	Microwave
EN-BH25W/40	25	4000	1800	72	120	White	Non Dimmable
EN-BH25W/40EM	27	4000	1800	67	120	White	Emergency
EN-BH25W/40EMMS	27	4000	1800	67	120	White	Emergency Microwave
EN-BH25W/40MS	25	4000	1800	72	120	White	Microwave

## Line Drawing

## Polar Curve

## Colour



Black

White

## Feature &amp; Benefits

- IP66 LED bulkhead not affected by frequent switching
- IK10 polycarbonate body and diffuser
- Rear entry access wiring compartment allows for easy installation
- Interchangeable eyelid bezel accessory available
- Separate 20mm conduit side entry
- Wall or ceiling mounted - accessories included
- Emergency and microwave options available
- Adjustable light detector from 2-50 lux
- Adjustable hold time 5 seconds to 30 minutes
- 1.5kV surge protection
- 5 year warranty

## Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP66
Lifetime L70 (hrs)	30000hrs	IK Rating	IK10
Lamp Base	None	Overall Diameter (mm)	360
Weight (Kg)	1.624	Projection (mm)	105
Product Type	Bulkheads	Operating Temp. (Min) °C	-25°C
Operating Temp. (Max) °C	40°C		

## Compliance &amp; Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.