



SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour	Product Type
EN-BTW1544/40	4000	4100	94	44	120	White	Non Dimmable

Line Drawing



Polar Curve



Color

Product Features:

- Steel housing and high quality polycarbonate diffuser eliminate hot spots providing uniformed low glare light output
- Perfect for retrofitting existing or as an alternative to T8 or T5 fluorescent fittings
- Twin version available with winged reflectors for reduced glare
- Through wiring with side and rear cable entry
- Integrated driver supplied in housing
- Available in typical 1200mm, 1500mm and 1800mm lengths
- 1.5kV surge protection
- 3 years warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.95	Dimmable	No
IP Rating	IP20	Technology	LED
Luminaire Distribution	Direct	Lifetime L70 (hrs)	35000
IK Rating	IK05	Operating Temp	30°C
Optic Material	PC	Lamp Base	Other
Width (mm)	85	Length (mm)	1520
Weight (Kg)	2.610	Positional Adjustment	Fixed
SDCM	6	Positional Adjustment	Fixed

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.